

50Hz SME Generator Set Specification

Genset Model	Standby Power		Prime Power		Engine Model	Displacement (L)	Fuel Consumption (L/h)		
	kVA	kW	kVA	kW				L*W*H (mm)	L*W*H (mm)
TMC750	738	590	660	530	S6R2-PTA-C	29.96	123	4100*1720-	6058*2438*2591
TMC825	825	660	750	600	S6R2-PTAA-C	29.96	148	4100*1720-	6058*2438*2591
TMC1375	1375	1100	1250	1000	S12R-PTA-C	49.03	235	4505*2210*231	12192*2438*289
TMC1500	1500	1200	1375	1100	S12R-PTA2-C	49.03	259	4505*2200*240	12192*2438*289
TMC1650	1650	1320	1500	1200	S12R-PTAA2-C	49.03	317	5000*2226*258	12192*2438*289
TMC1900	1873	1498	1710	1370	S16R-PTA-C	65.37	351	5340*2250*251	12192*2438*289
TMC2000	2000	1600	1875	1500	S16R-PTA2-C	65.37	388	5350*2250*288	
TMC2250	2250	1800	2000	1600	S16R-PTAA2-C	65.37	415	5750*2135*286	
TMC2500	2500	2000	2273	1818	S16R2-PTAW-	79.9	464	5980*2200*300	